

PRODUCT FICHE ACCORDING TO COMMISSION DELEGATED REGULATION (EU) NO 65/2014



NEW

WISH MWR 32 BIA AB



Microwave + grill

- Capacity, gross/net: 38/32 litres
- Stainless steel cavity
- Minute minder
- 3 cooking functions
- 5 Power levels, 1.000 W
- 1.500 W drop down grill
- 0-60 min. Timer
- Keep warm & pizza functions
- Defrost by time
- Automatic disconnection security system
- Triple glazed door
- 2 round grid with feet and browning plate
- Integrated rotary turntable, 32 cm
- Tangential ventilation

COLOR

Anthracite / Brass

EXTERNAL DIMENSIONS

455 mm 595 mm 472 mm



NEW

WISH MWR 32 BIA BB



Microwave + grill

- Capacity, gross/net: 38/32 litres
- Stainless steel cavity
- Minute minder
- 3 cooking functions
- 5 Power levels, 1.000 W
- 1.500 W drop down grill
- 0-60 min. Timer
- Keep warm & pizza functions
- Defrost by time
- Automatic disconnection security system
- Triple glazed door
- 2 round grid with feet and browning plate
- Integrated rotary turntable, 32 cm
- Tangential ventilation

COLOR

Beige / Brass

EXTERNAL DIMENSIONS

455 mm 595 mm 472 mm



NEW

WISH MWR 32 BIA VB



Microwave + grill

- Capacity, gross/net: 38/32 litres
- Stainless steel cavity
- Minute minder
- 3 cooking functions
- 5 Power levels, 1.000 W
- 1.500 W drop down grill
- 0-60 min. Timer
- Keep warm & pizza functions
- Defrost by time
- Automatic disconnection security system
- Triple glazed door
- 2 round grid with feet and browning plate
- Integrated rotary turntable, 32 cm
- Tangential ventilation

COLOR

Bright cream / Brass

EXTERNAL DIMENSIONS

455 mm 595 mm 472 mm

MODELS	HLC 860 P	HSC 635 P	HBC 625 P	HLC 840	HSC 635	HBC 535	HLC 847 SC
Energy Efficiency Index (EEI)	80,8	80,8	80,8	80,8	80,8	102,7	
Energy Efficiency Class	A+	A+	A+	A+	A+	A	A+
Energy consumption per cycle in conventional mode (kWh)	0,77	0,77	0,77	0,72	0,77	0,77	
Energy consumption per cycle in fan-forced convection mode (kWh)	0,59	0,59	0,59	0,59	0,59	-	
Number of cavities	1	1	1	1	1	1	1
Heat source	Electric	Electric	Electric	Electric	Electric	Electric	Electric
Volume (l)	44	44	44	44	44	48	44

DIMENSIONS

External, mm	455x595x 559	455x595x 559	455x595x 559	455x595x 559	455x595x 559	455x595x 559	455x595x 559
Inner cavity, mm	232x475x405	232x475x405	232x475x405	232x475x405	232x475x405	232x475x441	232x475x405

CLEANING SYSTEMS

DualClean	*	*	*	-	-	-	-
Pyrolytic	*	*	*	-	-	-	-
HydroClean®	PRO	PRO	PRO	PRO	PRO	ECO	PRO
Esmalte	Slippery	Slippery	Slippery	Slippery	Slippery	Slippery	Slippery

FEATURES

Type	Pyrolytic Multifunction Turbo	Pyrolytic Multifunction	Pyrolytic Multifunction	Multifunction Turbo	Multifunction	Conventional	Multifunction Turbo + Steamer
Stainless steel (fingerprint proof)	*	*	*	*	*	*	*
Cooking functions	12	8	8	9	8	3	15
Temperature regulator	30-270°	50-250°	50-250°	50-250°	50-250°	50-250°	30-270°
Touch Control	• / TFT 4"	• / LED display	• / LED display	• / LED display	• / LED display	Minute Minder	• / TFT 4"
LED ring illuminated knobs	*	-	-	-	-	-	*
SoftClose	-	-	-	-	-	-	*
Recipes	20 recipes	-	-	-	-	-	20 recipes
Meat probe	-	-	-	-	-	-	*
SlowCook: low temperature cooking	*	-	-	-	-	-	*
Tangential ventilation	*	*	*	Dynamic	Dynamic	Dynamic	*
Express quick heating	Automatic	*	*	*	*	-	Automatic
Telescopic guides	1 easy slide	1 easy slide	-	1 easy slide	1 easy slide	1 easy slide	1 easy slide
Drop-down grill	-	-	-	*	*	-	-
Light	25W	25W	25W	25W	25W	25W	25W

SAFETY SYSTEMS

Glazed door	4 removable	3 removable	3 removable	3 removable	3 removable	3 removable	3
Automatic disconnection security system	*	*	*	-	-	-	*
Children safety block, timer and door	*	*	*	Timer	Timer	Timer	*
Grill protection	*	*	*	*	*	*	*
Anti-tip tray system	*	*	*	*	*	*	*

ACCESORIES

MultiCook / cast aluminium tray	optional	optional	optional / *	optional	optional	optional / *	Gastronorm / optional
Anti-tip baking / deep tray (50 mm)	- / *	- / *	- / *	- / *	- / *	- / *	1 SS perforated / *
Anti-tip reinforced / cooking grid	* / -	- / *	- / *	* / -	- / *	- / *	*

POWER CONSUMPTION

Turbo, W	1.800	-	-	1.800	-	-	1.600
Grill / Maxi grill, W	1.400/2.550	1.400/2.550	1.400/2.550	1.400/2.500	1.400/2.500	1.400/ -	1400/2500
Traditional, W	2.450	2.450	2.450	2.550	2.550	2.550	2.100
Multifunction motor, W	25	25	25	22	22	-	30
Bottom heat, W	1.050	1.050	1.050	1.150	1.150	1.150	1.000
Cooling fan motor, W	30	30	30	18	18	18	18
Mwo power, W	-	-	-	-	-	-	-

ELECTRICAL FEATURES

Voltage, V	220/240	220/240	220/240	220/240	220/240	220/240	220-240
Frequency, HZ	50/60	50/60	50/60	50/60	50/60	50/60	50
Maximum connection rating, W	2.915	2.515	2.515	3.015	2.615	2.593	3.400
Cable connection length, cm	150 + Plug	110	110	110	110	110	110

1) In a scale embracing from A (more efficient) to G (less efficient). Commission directive 2002/40/EC. According to Norm EN50304: 2014 update 65/2014. Models that are steam only or including microwave not subject to legislation. Subject to change without notice.

PRODUCT FICHE ACCORDING TO COMMISSION DELEGATED REGULATION (EU) NO 65/2014

MODELS	HSC 644 S	HLC 849 C	HLC 847 C	HLC 844 C	HSC 644 C	MLC 844
Energy Efficiency Index (EEI)	-	-	-	-	-	-
Energy Efficiency Class	-	-	-	-	-	-
Energy consumption per cycle in conventional mode (kWh)	-	-	-	-	-	-
Energy consumption per cycle in fan-forced convection mode (kWh)	-	-	-	-	-	-
Number of cavities	1	1	1	1	1	1
Heat source	Eléctrica	Eléctrica	Eléctrica	Eléctrica	Eléctrica	Eléctrica
Volume (l)	48	40	40	40	40	44

**DIMENSIONS**

External, mm	455x595x 559	455x595x 559	455x595x 559	455x595x 559	455x595x 559	455x595x 559
Inner cavity, mm	232x475x405	232x475x365	232x475x365	232x475x365	232x475x365	232x475x405

**CLEANING SYSTEMS**

DualClean	-	-	-	-	-	-
Pyrolytic	-	-	-	-	-	-
HydroClean®	-	PRO	PRO	ECO	ECO	-
Esmalte	Slippery	Slippery	Slippery	Slippery	Slippery	Slippery

**FEATURES**

Type	Steam oven	Combi MF Turbo + Microwave	Combi MF Turbo + Microwave	Combi MF Turbo + Microwave	Combi MF Turbo + Microwave	Microwave + grill
Stainless steel (fingerprint proof)	•	•/Black	•/Black	•/Black	•	•/Black
Cooking functions	1	22	16	11	11	3
Temperature regulator	30-100°	30-270°	30-270°	50-250°	50-250°	-
Touch Control	• / LED display	• / TFT 5"	• / TFT 4"	• / LED display	• / LED display	• / LED display
LED ring illuminated knobs	-	-	•	-	-	-
SoftClose	-	•	•	-	-	-
Recipes	-	50 recipes	20 recipes	-	-	-
Meat probe	-	•	-	-	-	-
SlowCook: low temperature cooking	-	•	•	-	-	-
Tangential ventilation	•	•	•	•	•	•
Express quick heating	-	Automatic	Automatic	-	-	-
Telescopic guides	-	1 easy slide	1 easy slide	-	-	-
Drop-down grill	-	-	-	-	-	-
Light	25W	25W	25W	25W	25W	25W

**SAFETY SYSTEMS**

Glazed door	3 full	3	3	3	3	2
Automatic disconnection security system	•	•	•	•	•	•
Children safety block, timer and door	•	•	•	•	•	-
Grill protection	-	•	•	•	•	•
Anti-tip tray system	•	•	•	•	•	•

**ACCESORIES**

MultiCook / cast aluminium tray	-	-	-	-	-	-
Anti-tip baking / deep tray (50 mm)	1 SS perforated / •	glass	glass	glass	glass	-
Anti-tip reinforced / cooking grid	•	•	•	•	•	•

**POWER CONSUMPTION**

Turbo, W	-	1.600	1.600	1.600	1.600	-
Grill / Maxi grill, W	-	1400/2500	1400/2500	-/2500	-/2500	1.400
Traditional, W	-	2.100	2.100	2.100	2.100	-
Multifunction motor, W	-	30	30	30	30	-
Bottom heat, W	1000 (just for water rec.)	1.000	1.000	-	-	-
Cooling fan motor, W	18	18	18	18	18	18
Mwo power, W	-	1000	1000	1000	1000	1000

**ELECTRICAL FEATURES**

Voltage, V	220-240	220-240	220-240	220-240	220-240	220-240
Frequency, HZ	50	50	50	50	50	50
Maximum connection rating, W	2.300	3.400	3.400	3.400	3.400	3.200
Cable connection length, cm	110	110	110	110	110	110

MODELS	MSC 642	MWR 32 BIA AB/BB/VB
Energy Efficiency Index (EEI)	-	-
Energy Efficiency Class	-	-
Energy consumption per cycle in conventional mode (kWh)	-	-
Energy consumption per cycle in fan-forced convection mode (kWh)	-	-
Number of cavities	1	1
Heat source	Eléctrica	Eléctrica
Volume (l)	44	38

**DIMENSIONS**

External, mm	455x595x 559	455x595x472
Inner cavity, mm	232x475x405	210x420x390

**CLEANING SYSTEMS**

DualClean	-	-
Pyrolytic	-	-
HydroClean®	-	-
Esmalte	Slippery	-

**FEATURES**

Type	Microwave + grill	Microwave + grill
Stainless steel (fingerprint proof)	•	Anthracite / Beige / Bright cream - Brass
Cooking functions	3	3 + Keep warm, pizza & automatic defrost by time
Temperature regulator	-	-
Touch Control	Minute minder	Minute minder
LED ring illuminated knobs	-	-
SoftClose	-	-
Recipes	-	-
Meat probe	-	-
SlowCook: low temperature cooking	-	-
Tangential ventilation	•	•
Express quick heating	-	-
Telescopic guides	-	-
Drop-down grill	-	•
Light	25W	20W

**SAFETY SYSTEMS**

Glazed door	2	3
Automatic disconnection security system	•	•
Children safety block, timer and door	-	-
Grill protection	•	-
Anti-tip tray system	•	-

**ACCESORIES**

MultiCook / cast aluminium tray	-	-
Anti-tip baking / deep tray (50 mm)	-	-
Anti-tip reinforced / cooking grid	•	2 round grip with feet, browning plate and turntable

**POWER CONSUMPTION**

Turbo, W	-	-
Grill / Maxi grill, W	1.400	1.500
Traditional, W	-	-
Multifunction motor, W	-	-
Bottom heat, W	-	-
Cooling fan motor, W	18	35
Mwo power, W	1000	1000

**ELECTRICAL FEATURES**

Voltage, V	220-240	220-240
Frequency, HZ	50	50
Maximum connection rating, W	3.200	3.300
Cable connection length, cm	110	150

	CLC 855 GM	CLC 835 MC
Multi capsule	-	•

**DIMENSIONS**

Height, mm	455	455
Width, mm	595	595
Depth, mm	413	330
Cabinet height, mm	450	450
Cabinet width, mm	560	560
Cabinet depth, mm	580	580

**FEATURES**

Type	Built-in coffee maker	Multi capsule built-in coffee maker
Stainless steel (fingerprint proof)	• / black	• / black
Electronic	•	• / TFT 4"
Knobs	2	2
Number of cups	2	1
Height adjustable cup	•	•
Grinded coffee	•	•
Coffee capsules	-	•
Retractable pipe for Steam and hot water	•	•
Capacity of Water Tank	1,8 litres	1 litre
Functions to select:	-	-
On / Off	•	•
Steam	•	•
Coffee Type	large, medium and small	extra large, large, medium, small and infusions
Telescopic guides	•	-
LED lighting	•	•
Coffee Temperature	•	•
Pump pressure	15 bar	19 bar

**INDICATIONS ON DISPLAY**

Selected function	•	•
Fill water tank	•	•
Descaling	•	•

**STANDARD ACCESORIES**

Capsule and Coffee adapters	-	5
-----------------------------	---	---

**ELECTRICAL FEATURES**

Tension V 230	230	230
Frequency Hz 50-60	50-60	50-60
Maximum Nominal Power 2100	1350	2100
Connecting Cable (cm)	130 + schuko	110 + schuko