

MODEL	ML 822 BIS L	ML 822 BIS R	ML 822 BIS L WHITE	MS 622 BIS L	MS 622 BIS R	MS 622 BI
Type	Microwave + Grill	Microwave + Grill	Microwave + Grill	Microwave + Grill	Microwave + Grill	Microwave
Volume, l	22	22	22	22	22	22

DIMENSIONS

Height, mm	390	390	390	390	390	390
Width, mm	595	595	595	595	595	595
Depth, mm	334	334	334	334	334	334
Inner height, mm	280	280	280	280	280	280
Inner width, mm	350	350	350	350	350	350
Inner depth, mm	220	220	220	220	220	220

FEATURES

Stainless steel (fingerprint proof)	• / Black	• / Black	• / White	•	•	•
Control	Electronic Control panel with LED display	Electronic Control panel with LED display	Electronic Control panel with LED display	Touch Control panel with LED display	Touch Control panel with LED display	Electromechanical controls
Electronic door opening	•	•	•	•	•	•
Cooking functions	3	3	3	3	3	1
Grill	Grill	Grill	Grill	Grill	Grill	-
Microwave	Microwave	Microwave	Microwave	Microwave	Microwave	Microwave
Microwave+Grill	Microwave+Grill	Microwave+Grill	Microwave+Grill	Microwave+Grill	Microwave+Grill	-
Microwave power levels	5	5	5	5	5	5
Direct access menu	9	9	9	2	2	-
Memories	-	-	-	-	-	-
Defrosting by weight	•	•	•	•	•	-
Defrosting by time	•	•	•	•	•	•
Quick start	+30"	+30"	+30"	+30"	+30"	-
Minute minder	0-90'	0-90'	0-90'	0-90'	0-90'	0-60'
Drop-down grill	•	•	•	•	•	-
Stainless steel cavity	•	•	•	•	•	•
Ceramic base	•	•	•	•	•	•
Turntable	-	-	-	-	-	-
Tangential ventilation	•	•	•	•	•	•
Door opening	Left	Right	Left	Left	Right	Left

SAFETY SYSTEMS

Glazed door	Double	Double	Double	Double	Double	Double
Automatic disconnection security system	•	•	•	•	•	•
Children safety block, timer and door	•	•	•	•	•	-
Grill protection	•	•	•	•	•	-
Safety thermostat	•	•	•	•	•	•

ACCESORIES

Grid with feet	1	1	1	1	1	-
Browning plate	•	•	•	-	-	-

POWER CONSUMPTION

Grill / Maxi grill, W	1200	1200	1200	1200	1200	-
Microwave power	850	850	850	850	850	850

ELECTRICAL FEATURES

Voltage, V	220-240	220-240	220-240	220-240	220-240	220-240
Frequency, HZ	50	50	50	50	50	50
Maximum connection rating, W	2500	2500	2500	2500	2500	1400
Cable connection length, cm	110cm + schuko	110cm + schuko	110cm + schuko	110cm + schuko	110cm + schuko	110cm + schuko

MODEL	ML 820 BIS	MS 620 BIS	ML 820 BI	MS 620 BIH	MB 620 BI	MWR 22 BI AB/BB/VB MWR 22 BI AB/BB/VB
Type	Microwave + Grill	Microwave + Grill	Microwave	Microwave	Microwave	Rustic
Volume, l	20	20	20	20	20	22

DIMENSIONS

Height, mm	390	390	390	390	390	390
Width, mm	595	595	595	595	595	595
Depth, mm	325	325	325	325	325	334
Inner height, mm	210	210	210	210	210	220
Inner width, mm	305	305	305	305	305	350
Inner depth, mm	280	280	280	280	280	280

FEATURES

Stainless steel (fingerprint proof)	• / Black	•	• / Black	•	• / White	Anthracite / Beige / Bright Cream-Brass
Control	Touch Control panel with TFT white display	Touch Control panel with TFT white display	Electromechanical controls	Electronic controls with white display	Electromechanical controls	Electromechanical controls
Electronic door opening	-	-	-	-	-	•
Cooking functions	3	3	1	1	1	1
Grill	Grill (Quartz)	Grill (Quartz)	-	-	-	-
Microwave	Microwave	Microwave	Microwave	Microwave	Microwave	Microwave
Microwave+Grill	Microwave+Grill	Microwave+Grill	-	-	-	-
Microwave power levels	5	5	5	5	5	5
Direct access menu	3	3	-	3	-	-
Memories	1	1	-	1	-	-
Defrosting by weight	•	•	-	•	-	-
Defrosting by time	•	•	•	•	•	•
Quick start	+30"	+30"	-	+30"	-	-
Minute minder	0-90'	0-90'	0-60'	0-90'	0-60'	0-60'
Drop-down grill	-	-	-	-	-	-
Stainless steel cavity	•	•	•	•	•	•
Ceramic base	-	-	-	-	-	•
Turntable	24 cm	24 cm	24 cm	24 cm	24 cm	-
Tangential ventilation	-	-	-	-	-	•
Door opening	Left	Left	Left	Left	Left	Left

SAFETY SYSTEMS

Glazed door	Double	Double	Double	Double	Double	2
Automatic disconnection security system	•	•	•	•	•	•
Children safety block, timer and door	•	•	-	-	-	-
Grill protection	-	-	-	-	-	-
Safety thermostat	•	•	•	•	•	•

ACCESORIES

Grid with feet	1 Round	1 Round	-	-	-	-
Browning plate	-	-	-	-	-	-

POWER CONSUMPTION

Grill / Maxi grill, W	1000	1000	-	-	-	-
Microwave power	700	700	700	700	700	850

ELECTRICAL FEATURES

Voltage, V	220 - 240	220 - 240	220 - 240	220 - 240	220 - 240	220-240
Frequency, HZ	50	50	50	50	50	50
Maximum connection rating, W	1100	1100	1100	1100	1100	1400
Cable connection length, cm	110cm + schuko	110cm + schuko	110cm + schuko	110cm + schuko	110cm + schuko	150